

# GT150

## 8,000 PINS PER CHARGE OR 3,000 PINS PER CHARGE?

(Well, that's what we call a no-brainer.)

Nearly 3x the run rate as competing tools. Less charging downtime.

### BENEFITS:

- Power to shoot into concrete & steel
- Fuel cell delivers a 4-year shelf life, and 1,000 shots
- Lithium ion battery delivers 8,000 shots per charge – nearly 3x more than competing systems
- GTTPins are made with heat treated steel and MH galvanized for higher quality
- 1 hour battery recharge time
- No license required

### FEATURES:

- High performance gas powered tool
- 2 Lithium ion batteries included
- Battery life gauge included
- 4 year fuel cell shelf life
- Depth-of-drive adjustment
- ½" to 1-½" pin capacity
- Quick release 40-pin magazine
- Light weight
- Magnetic lath adaptor available
- Belt clip included
- 2-year warranty

### APPLICATIONS:

- Track to concrete and steel
- Plywood to concrete or block
- Furring strips to concrete or block
- Lath to block or concrete (with magnetic adaptor)



## GRABBER GTTPINS

|            |  |
|------------|--|
| GTTTP012   | .102 - .120 X 1/2" STEP SHANK ZINC STEEL PIN |
| GTTTP034   | .102 X 3/4" SMOOTH SHANK ZINC PIN            |
| GTTTFFP034 | .102 - .120 X 3/4" STEP SHANK ZINC PIN       |
| GTTTP100   | .102 X 1" SMOOTH SHANK ZINC PIN              |
| GTTTP114   | .102 X 1-1/4" SMOOTH SHANK ZINC PIN          |
| GTTTP112   | .102 X 1-1/2" SMOOTH SHANK ZINC PIN          |

ALL ITEMS ABOVE ARE 1M TO A BOX AND 5M TO A CASE - EACH 1M BOX CONTAINS ONE FUEL CELL

## FUEL CELL

|         |  |
|---------|--|
| GTTFUEL | GAS FUEL CELL FOR GTT150 AND GTT150HD (CASE OF 12) |
|---------|--|

## BATTERIES

|           |   |
|-----------|---|
| GTTBAT    | LI-ION BATTERY PACK FOR GTT150 AND GTT150HD TOOLS |
| GTTCHARGE | BATTERY CHARGER FOR GTT150 AND GTT150HD TOOLS     |

## LATH MAGNETIC ADAPTERS AND WASHERS

|        |   |
|--------|---|
| GTTLDW | 1" LATH DISC WASHER (1M PER BOX, 5M PER CASE) |
| GTTLA  | MAGNETIC LATH WASHER ADAPTER FOR GTT150       |

## FASTENER SPECIFICATIONS

|                  |  |
|------------------|--|
| GRABBER GTT PINS | 1/2" - 1-1/2"                              |
| SHANK DIAMETERS  | .102" - SMOOTH & .102" - .120" SMOOTH STEP |
| HEAD DIAMETER    | .250#                                      |

THE ABOVE PARTS FEATURE PLASTIC STRIP COLLATION AND OFFER 10 FASTENERS PER COLLATED UNIT.



### ALLOWABLE CAPACITY

| Part Number                               | Concrete Comprehensive Strength |       |          |       |
|---|---------------------------------|-------|----------|-------|
|   | 4000 PSI                        |       | 6000 PSI |       |
| GTTTP034, GTTTP100,<br>GTTTP114, GTTTP112 | TENSION                         | SHEAR | TENSION  | SHEAR |
|   | 52                              | 77    | 50       | 89    |
| Part Number                               | Steel Comprehensive Strength    |       |          |       |
|   | 1/4" THICK STEEL                |       |          |       |
| GTTTP012                                  | TENSION                         |       | SHEAR    |       |
|   | 162                             |       | 419      |       |

Values are based on the lowest ultimate load with a safety factor of 5.0 applied

TESTED TO:  
ASTM E 1190 - 11 SECTION 8.1 STANDARD  
TEST METHOD FOR STRENGTH OF POWER  
ACTUATED FASTENERS INSTALLED IN  
STRUCTURAL MEMBERS.  
ASTM E 18-12 STANDARD TEST METHOD FOR  
ROCKWELL HARDNESS OF METALLIC  
MATERIALS

CODE COMPLIANCE:  
MEETS OR EXCEEDS THE REQUIREMENTS OF  
SECTION 9.27.5.7 OF THE 2010 NATIONAL  
BUILDING CODE OF CANADA.