



Installation Guidelines for Grabber GTPINs

Make Certain the Grabber GTT150 or GTT150HD Gas Tool is in a Safe and Useable Condition Based on Operating Manual Guidelines

Inspect the GTT150 or GTT150HD gas tool thoroughly to make certain all mechanisms are in working order. This includes a fully charged battery and an active fuel cell coded within the expiration period.

Compress tool to surface to be certain nosepiece depresses and retracts easily. Once depressed the fan motor will begin to turn to ensure tool is active and ready for use.

Slide only Grabber GTPINs through the magazine with a maximum of four ten pin strips. Release follower and the GTT150 or GTT150HD is ready to fire.

Choosing the Correct Fastener for Specific Applications

Determine appropriate Grabber GTPIN for the application at hand. Based on base material hardness and or project specifications, installing the correct GTPIN will assure a tight and secure fastening to the work surface. Certain fasteners will work better in hard concrete applications and a specific steel pin has been designed for structural attachment. Consult Grabber guidelines when choosing the necessary pin.

Always Keep the GTT150 or GTT150HD Tool in a Perpendicular Position to the Work Surface and Level at all Times

The GTT150 or GTT150HD gas tool should always be held in a perpendicular position to the work surface. A leveling leg is also provided on the tool to be certain it is level during the firing sequence. Press the tool firmly against the steel track compressing it firmly against the concrete, block or steel base material. This will assure a tight fastening. Depress trigger that will drive the appropriate fastener in to the surface. Continue same procedure typically on 16" centers until entire track is firmly fastened into place.

Grabber Construction Products Inc.
5355 West 11000 North
Highland, Utah 84003
Phone: 800-477-8876
Fax: 801-349-4799