

PRODUCT SUBMITTAL

Submitted to:

Project:

Date of Submittal:

Submitted by, Contact name:

Company:

Address:

Phone:

Email:

Approved

Approved as Noted

Not Approved

Comments:

By:

Date:

List of items from Table A submitted for the project:

--

Product Family: PSF - Self-Piercing Scavenger Head Fine Thread

TABLE A

Item Number	Screw Size (#)	Length	Head Style	Head/Washer Diameter (in.)	TPI	Point Size/Style	Coating	Maximum Drilling Capacity (in.)	Drive Type	Bulk/Collated Quantity
168S	6	1-in	Scavenger®	0.325	15	Streaker®	Phosphate	0.033	#2 Phillips	10,000
268S	6	1-1/8-in	Scavenger®	0.325	15	Streaker®	Phosphate	0.033	#2 Phillips	10,000
268SV	6	1-1/8-in	Scavenger®	0.325	15	Vector	Phosphate	0.033	#2 Phillips	10,000
368S	6	1-1/4-in	Scavenger®	0.325	15	Streaker®	Phosphate	0.033	#2 Phillips	8,000
368SV	6	1-1/4-in	Scavenger®	0.325	15	Vector	Phosphate	0.033	#2 Phillips	8,000
C368S	6	1-1/4-in	Scavenger®	0.325	15	Streaker®	Phosphate	0.033	#2 Phillips	1,000
C368SV	6	1-1/4-in	Scavenger®	0.325	15	Vector	Phosphate	0.033	#2 Phillips	1,000
C368SVZ	6	1-1/4-in	Scavenger®	0.325	15	Vector	Clear Zinc	0.033	#2 Phillips	1,000
468S	6	1-5/8-in	Scavenger®	0.325	15	Streaker®	Phosphate	0.033	#2 Phillips	5,000

Grabber screws manufactured in America are available as SPECIAL-ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY. For identification purposes, an "A" will be added to the end of the item number and "Made in America" will be printed on the label.

Prefixes: X = 1-lb, VB = 5-lb, BP = Blister Pack, C = Collated

Suffixes: S = Scavenger® Head, V = Vector Point, Z = Clear Zinc, XX = 20-lb.

Description: Scavenger head Streaker thread screw used in light-gauge (see TABLE A - Maximum Total Drilling Thickness) steel and wood applications. The self-tapping Streaker (twin thread, single lead) design results in faster penetration into light-gauge steel and wood.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance - Sizes #6, up to 4,000 RPM. For gypsum board, the Scavenger head is fully seated when the screw is below the surface of the wallboard in accordance with Section 7.2.2 of ASTM C1002. Overdriving may result in failure of the fastener. The fastener must penetrate beyond the metal a minimum of three full threads.

Corrosion: For Corrosion Resistance Testing Results, see TABLE B.


Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. PSF fasteners are used for gypsum board to light-gauge steel and gypsum board to wood applications and comply with ASTM C1002 and ASTM C1002 requirements.

PSF - Self-Piercing Scavenger Head Fine Thread



Streaker Thread

Twin Thread, Single Lead design for faster installation
(Requires one-half of the rotations as regular thread design)



Vector Point

Very High-Speed penetration design for even faster installation

NOTE: The Scavenger head is a special bugle-style head design that eliminates troubling paper burrs in gypsum board.

TABLE B

CORROSION RESISTANCE TESTING RESULTS			
Finish	Test	Standard/Protocol	Results (minimum)
Phosphate	Salt Spray	ASTM B117	24 hours, no red rust

NOTE: Salt Spray Testing (SST) results are not intended to predict corrosion resistance in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool to compare different metals and different metal coatings in a tightly controlled highly corrosive environment for specific periods of time. For more information about corrosion resistance, see the *Grabber Guide to Corrosion Resistance for Fasteners*.

Grabber's approved mills keep tight control over all production standards and processes. Grabber's mills are ISO 9001 ensuring Grabber fasteners meet or exceed the highest industry standards.

TRADEMARKS:

The following registered trademarks used herein are owned by Grabber Construction Products, Inc.:

GRABBER®
Scavenger®
Streaker®

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.