

PRODUCT SUBMITTAL

Submitted to:

Project:

Date of Submittal:

Submitted by, Contact name:

Company:

Address:

Phone:

Email:

Approved

Approved as Noted

Not Approved

Comments:

By:

Date:

List of items from Table A submitted for the project:

--

Product Family: PTH - Self-Piercing Trim Head Hi-Lo Thread

TABLE A

Item Number	Screw Size (#)	Length	Head Style	Head Diameter (in.)	TPI	Point Size/Style	Coating	Maximum Drilling Capacity (in.)	Drive Type	Collated Quantity
C7125UL2	7	1-1/4-in	Flat	0.276	16 Hi-Lo	TwinFast	Phosphate	0.033	#2 LOX	1,000

Grabber screws manufactured in America are available as SPECIAL-ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY. For identification purposes, an "A" will be added to the end of the item number and "Made in America" will be printed on the label.

Prefixes: X = 1-lb, VB = 5-lb, BP = Blister Pack, C = Collated

Description: Trim head TwinFast Hi-Lo thread screw with underhead nibs used in underlayment-to-wood or light-gauge steel (see TABLE A - Maximum Total Drilling Thickness) applications. Self-tapping Sharp is designed for penetration into wood or light-gauge steel.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance - Sizes #7, up to 4,000 RPM. Overdriving may result in failure of the fastener. The fastener must penetrate beyond the metal a minimum of three full threads.

Corrosion: For Corrosion Resistance Testing Results, see TABLE B.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. PFH fasteners comply with ASTM C1513 requirements.


PTH - Self-Piercing Trim Head Hi-Lo Thread



Four Nibs
Under Head



#2 LOX
Recess



Hi-Lo Thread Design for broader applications
Twin Thread, Double Lead for faster penetration

TABLE B

CORROSION RESISTANCE TESTING RESULTS			
Finish	Test	Standard/Protocol	Results (minimum)
Phosphate	Salt Spray	ASTM B117	24 hours, no red rust

NOTE: Salt Spray Testing (SST) results are not intended to predict corrosion resistance in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool to compare different metals and different metal coatings in a tightly controlled highly corrosive environment for specific periods of time. For more information about corrosion resistance, see the *Grabber Guide to Corrosion Resistance for Fasteners*.

Grabber's approved mills keep tight control over all production standards and processes. Grabber's mills are ISO 9001 ensuring Grabber fasteners meet or exceed the highest industry standards.

TRADEMARKS:

The following registered trademarks used herein are owned by Grabber Construction Products, Inc.:

GRABBER®

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.