

## PRODUCT SUBMITTAL

**Submitted to:**

Project:

Date of Submittal:

**Submitted by, Contact name:**

Company:

Address:

Phone:

Email:

Approved

Approved as Noted

Not Approved

Comments:

By:

Date:

---

List of items from Table A submitted for the project:

--

**Product Family: DWCC - Drywall Nail Cement Coated Diamond Point**

**Table A**

Item Number	Gauge (#)	Wire Diameter	Head Size	Length	Shank Type	Head Type	Point Type	Finish	LBS/CTN	Application
DWCC125-25	13	0.091-in.	3/8-in.	1-1/4-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	25-lbs.	Attaching gypsum board to wood.
DWCC138	13	0.091-in.	3/8-in.	1-3/8-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.
DWCC138-25	13	0.091-in.	3/8-in.	1-3/8-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	25-lbs.	Attaching gypsum board to wood.
DWCC150	13	0.091-in.	3/8-in.	1-1/2-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.
DWCC178	13	0.091-in.	3/8-in.	1-7/8-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.
DWCC200	13	0.091-in.	3/8-in.	2-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.
DWCC238	13	0.091-in.	3/8-in.	2-3/8-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.
DWCC125H	12.5	0.099-in.	11/32-in.	1-1/4-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.
DWCC200125G	12.5	0.099-in.	11/32-in.	2-in.	Smooth	Flat Round	Long Sharp Diamond	Cement Coated	50-lbs.	Attaching gypsum board to wood.

**Prefix:** X = 1-lb., V = 5-lb., VB = 5-lb. Bucket


**Description:** Cement-coated drywall nails with long sharp diamond point used for attaching gypsum board to wood.

**Directions:** Install gypsum panels in accordance with ASTM C840 - *Standard Specification for Application and Finishing of Gypsum Board* and manufacturer's installation instructions/specifications.

**Corrosion Resistance:** Interior use only.

**Certifications:** All GRABBER® nail products are manufactured in facilities that are ISO 9001 certified. Cement-coated drywall nails with long sharp diamond point meet ASTM F1667 and ASTM C514 requirements.

**DWCC - Drywall Nail Cement Coated Diamond Point**



**TRADEMARKS:**

The following registered trademarks used herein are owned by Grabber Construction Products, Inc.:

GRABBER®

**NOTICE:**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.