

# SUBMITTAL SHEET

Submittal Sheet #ALSP2015

## **Item Name EYELAG Self Piercing with Shoulder**

Product:	ITEM#	DESCRIPTION	UNIT PACK
	ALSP234	1/4"x 2 3/4" Eye Lag Self Piercing with shoulder	1m
	ALSP314	1/4"x 3 1/4" Eye Lag Self Piercing with shoulder	1m
	ALSP234CP	1/4"x 2 3/4" Eye Lag Self Piercing with shoulder	CP
	ALSP314CP	1/4"x 3 1/4" Eye Lag Self Piercing with shoulder	CP

#### **USES**

ALSP eye lag screws are used to provide a means of attaching steel wire to the underside of unfilled steel deck for installation of suspended ceiling systems complying with IBC Section 808 1. The fasteners may be used where an engineered design is submitted in accordance with IRC Section R301 1 3

#### **DESCRIPTION**


General: ALSP screws are self-drilling tapping screws the screw have a self-drilling point and a self-tapping threaded shank below a washer-like collar.

### **INSTALLATION**

The ALSP screws must be installed in accordance with this report and the manufacturer's published installation instructions. A copy of these instructions must be available on the Jobsite at all times during installation

The screws and ceiling wire must be installed vertically to ensure that the tension load is applied along the axis of the screw, the screws must be installed perpendicular to the supporting steel deck material. through the upper or lower flute, using a screw driving tool When using a screw- driving pole toot recommended by the manufacturer, the installation speed must not exceed 200 rpm The ALSP screws may also be installed with a variable-speed drill With a maximum speed of 1900 rpm by using a special driver provided by the report holder

Screws must be spaced a minimum of 3/4 inch (19.1 mm) on center along the length of the deck panel and must be installed a minimum of 31 inch (19.1 mm) from the deck web After installation a minimum of three threads must protrude through the steel deck panel





Submittal Sheet #ALSP2015

Submittal Approvals:				
Job Name				
Contractor	Date			
TRADEMARKS:	Notice:			
The following trademark used herein is owned by	We shall not be liable for incidental and consequential			
Grabber Construction Products, Inc.: GRABBER.	damages, directly or indirectly sustained, nor for any loss			
	caused by application of these goods not in accordance with current printed instruction or for other than the			
	intended use. Our liability is expressly limited to			
	replacement of defective goods. Any claim shall be (30)			
	days of the date it was or reasonably should have been			
	discovered.			