


Galvanized Ring Shank Drywall Nails

Drywall to Wood









Description

Attaches gypsum board to wood.

Specifications

Size | Gauge: 12.5 and 13 **Length:** 1 1/4 in. and 2 in. Head Type: Flat Round Shank Type: Ring Finish: Galvanized

Quality Assurance: Grabber® fasteners are manufactured in ISO 9001 and ISO 14001 certified and approved factories.

LEED Reporting: The post-consumer recycled steel content is 25%.

Compliance: The fasteners comply with ASTM F1667 performance requirements.

Applications

■ 3/8 in., 1/2 in., and 5/8 in. single-layer gypsum board to wood studs

■ 1/2 in. and 5/8 in. double-layer gypsum board to wood

Installation

■ The head is fully seated when it's just below the surface of the gypsum board.


Features

- Flat round head provides a large area to hold the gypsum board securely.
- Ring shank nails have robust holding power. As the nail penetrates wood, fibers lock around the grooves in the shank, creating a durable bond.
- Long, diamond-shaped point is designed to easily drive into wood, and it helps prevent splitting.

Galvanized Ring Shank Drywall Nails

Drywall to Wood





Product Dimensions

Nail Gauge	B Head Diameter	Wire Diameter		
13	0.2969 in.	0.099 in.		
12.5	0.2969 in.	0.099 in.		

Ordering Information and Product Options

Item No.	Size	Head Type	Head Diameter	Gauge	Shank Type	Quantity	Weight	Special Features
Galvanized								
DWRS125-13G	1 1/4 in.	Flat Round	0.2969 in.	13	Ring	16,000	50 lb.	
DWRS125G	1 1/4 in.	Flat Round	0.2969 in.	12.5	Ring	16,000	50 lb.	
DWRS125B	1 1/4 in.	Flat Round	0.2969 in.	12.5	Ring	16,000	50 lb.	Dlue
DWRS200B	2 in.	Flat Round	0.2969 in.	12.5	Ring	10,000	50 lb.	Blue

Note: Product availability is subject to change without prior notice, and the availability of products may differ from what is printed in literature and displayed on our website. The items listed are bulk size. Most are also available in smaller package sizes such as 5 lb. and 1 lb. Contact your local Grabber Branch or Grabber Pro for more information.

Galvanized Ring Shank Drywall Nails PS1065 USA-ENG/Rev. 02-25

GRABBER CONSTRUCTION PRODUCTS, INC. 5255 W 11000 N., STE 100 HIGHLAND, UT 84003

(800) 477-8876 | GrabberPro.com

 $\textbf{SAFETY FIRST:} \ We ar appropriate personal protective equipment. Read applicable SDS and literature before$

TECHNICAL INFORMATION: Technical information contained herein is furnished without charge or obligation and is given and accepted at the recipient's sole risk. Because conditions of use may vary and are beyond our control, Grabber Construction Products makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with uses of any product described herein. Grabber $Construction\ Products\ reserves\ the\ right\ to\ modify\ this\ document\ without\ prior\ notice.$







