

Bugle Head Laminator

Gypsum Board to Gypsum Board









| Description | Used for the temporary attachment of gypsum board to gypsum board. Attaches |
|-------------|---|
| | adhesively laminated gypsum board to gypsum board. |

| Applications | Multilayered adhesively laminated gypsum board-to-gypsum board partitions |
|--------------|---|
| | Coreboard-to multilayered elevator shaft liners |
| | Not recommended for double-layered 3/8 in. panels |

| Installation | Use a standard screw gun with a depth-sensitive nose piece. Suggested screw gun specification for optimal performance: size #10, up to | For gypsum board, the bugle head is fully seated when the screw is below the surface of the wallboard, in accordance with ASTM C1002. |
|--------------|---|---|
| | 4,000 RPM. | Overdriving may result in failure of the fastener or failure of the gypsum board. |

A coarse thread screw for temporarily fastening one layer of drywall to another.

Features

- Extra-sharp, single lead 23° Grabber® point, designed to penetrate quickly and easily.
- Grabber's Pro-Fit #2 Phillips is a precision recess designed for better bit engagement, resulting in less wobble or strip-out.

Bugle Head Laminator

Gypsum Board to Gypsum Board



Standard Corrosion Test Results


| Finish | Test | Standard/Protocol | Results |
|-------------|------------|-------------------|----------------------|
| Phosphate | Salt Spray | ASTM B117 | 24 hrs., no red rust |
| Clear Zinc | Salt Spray | ASTM B117 | 12 hrs., no red rust |
| Yellow Zinc | Salt Spray | ASTM B117 | 24 hrs., no red rust |

Note: Salt Spray Testing (SST) results are not intended to predict corrosion in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool for comparing different metals and different metal coatings in a tightly controlled, highly corrosive environment for specific periods of time. For more information about corrosion resistance, refer to Grabber's Coatings and Corrosion Resistance Classifications in the Technical Data section of Grabber Fastener Solutions, PG1000. Consult with a corrosion specialist or the architect or engineer of record for detailed guidance and recommendations specific to your project.

D1 Minor Dia

D2 Major Dia

TDI¹



ad Di

Product Dimensions

| ons | 0120 | | NUCCOO | | | |
|-----|--|-------------------------------|----------------------------|---------------------------|---------------------|---|
| | #10 | 0.343 in. | #2 Phillips | 0.132 in. | 0.190 in. | 8 |
| | ¹ TPI stands for Threads Pe | r Inch. This is a count of th | e number of threads per in | ch measured along the ler | ngth of a fastener. | |

| ltem No. | Size | Recess | Head Dia. | TPI ¹ | Quantity | Weight | Special Features |
|-------------|----------------|-------------|-----------|-------------------------|----------|--------|------------------|
| Phosphate | | | | | | | |
| 12 | 10 x 1 1/2 in. | #2 Phillips | 0.343 in. | 8 | 5,000 | 39 lb. | |
| 12-2 | 10 x 2 in. | #2 Phillips | 0.343 in. | 8 | 1,000 | 22 lb. | |
| C12 | 10 x 1 1/2 in. | #2 Phillips | 0.343 in. | 8 | 1,000 | 52 lb. | Collated |
| C12-2 | 10 x 2 in. | #2 Phillips | 0.343 in. | 8 | 2,500 | 28 lb. | Collated |
| Clear Zinc | | | | | | | |
| 12Z | 10 x 1 1/2 in. | #2 Phillips | 0.343 in. | 8 | 5,000 | 39 lb. | |
| Yellow Zinc | | | | | | | |
| 12YZ | 10 x 1 1/2 in. | #2 Phillips | 0.343 in. | 8 | 5,000 | 39 lb. | |
| 12-2YZ | 10 x 2 in. | #2 Phillips | 0.343 in. | 8 | 1,000 | 22 lb. | |

¹TPI stands for Threads Per Inch. This is a count of the number of threads per inch measured along the length of a fastener.

Note: Product availability is subject to change without prior notice and the availability of products may differ from what is printed in literature and displayed on our website. The items listed are bulk size. Most are also available in smaller packages such as 5 lb. and 1 lb. Contact your local Grabber Branch or GrabberPro for more information.

Bugle Head Laminator PS1016 USA-ENG/Rev. 02-25

GRABBER CONSTRUCTION PRODUCTS, INC. 5255 W 11000 N., STE 100 HIGHLAND, UT 84003

(800) 477-8876 | GrabberPro.com

SAFETY FIRST: Wear appropriate personal protective equipment. Read applicable SDS and literature before handling and installation.



TECHNICAL INFORMATION: Technical information contained herein is furnished without charge or obligation and is given and accepted at the recipient's sole risk. Because conditions of use may vary and are beyond our control, Grabber Construction Products makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with uses of any product described herein. Grabber Construction Products reserves the right to modify this document without prior notice.



© 2025 Grabber Construction Products, Inc. | All rights reserved | Printed in U.S.A. The trademarks Grabber, and Stylized G on Grabber Fasteners, are trademarks of Grabber Construction Products, Inc.